



# Digital Signage Media Players

Website: [www.digitalimagingsource.com](http://www.digitalimagingsource.com)  
 Email: [sales@digitalimagingsource.com](mailto:sales@digitalimagingsource.com)



**LHD50**



**LHD56**



**LHD76**



**DMP-3**



**MP1080**

<b>LHD50 Palm Sized Media Player YPbPr 720p Output</b>	
• Video Format:	MPEG1: DAT, MPG, MPEG MPEG2: VOB, MPEG MPEG4: AVI, including DivX3-6, XviD
• Photo Format:	JPEG, BMP, GIF, PNG, TIFF
• Audio Format:	MP3, WMA, WAV
• External Subtitles:	SMI, SRT, ASS, SSA.
• Storage Options:	SD/MMC; USB2.0
• File System:	FAT16, FAT32, NTFS
• Input Interface:	USB (High speed USB2.0 host), SD/MMC
• Output Interface:	Audio: Stereo (Left and Right), SPDIF (coaxial) Video: CVBS (480i/576i) YCbCr/YPbPr (480i/480p/576i/576p/720p)
• OS Language:	English, French, German, Spanish, Italian, Portuguese, Polish, Swedish,
• Power Supply:	DC: 5V/1A; AC input: 110~240V, 50~60HZ
• Operating Temp:	0°C ~ 60°C
• Product Dimensions:	6.6 X 6.6 X 1.6 cm
• Contents Include:	LHD50, AV & YUV cable, 3.5mm Audio cable, power supply, remote control

<b>DMP-3 Media Player VGA/YPbPr 720p Output</b>	
• Video Format:	MPEG1, MPEG2, MPEG4 (Simple Profile) (up to 720x480 resolution)
• Photo Format:	JPEG, BMP, GIF, PNG, TIFF
• Audio Format:	MP3, WMA, WAV, AAC
• Storage Options:	Compact Flash
• File system:	FAT16, FAT32
• Input Interface:	Compact Flash
• Output Interface:	VGA (up to 1280x720 native resolution) YPbPr (576p, 720p,.)
• OS Language:	English, French, German, Spanish, Italian, Portuguese, Polish, Swedish,
• Power Supply:	DC: 5V/1A; AC input: 110~240V, 50~60HZ
• Operating Temp:	0°C ~ 60°C
• Product Dimensions:	132 x 25 x 91 mm
• Contents Include:	DMP-3, AV & VGA cable, Audio cable, power supply, remote control
* This player will loop both image and video file formats simultaneously.	

<b>LHD56 Palm Sized Media Player 1080i Output</b>	
• Video Format:	Divx3.11, 4.x, 5.x/Xvid/Avi/Mpeg/VOB/VCD/ISO (up to 800x600 resolution)
• Photo Format:	JPEG, BMP, GIF, PNG, TIFF
• Audio Format:	MP3( code rate 8Kbps - 320Kbps)/WMA/WAV/ACC/OGG
• External Subtitles:	SMI, SRT, ASS, SSA.
• Storage Options:	SD/SDHC/MMC/USB2.0 (connect to external hard disk)
• File system:	FAT16, FAT32, NTFS
• Input Interface:	USB (High speed USB2.0 host), SD / MMC
• Output Interface:	CVBS (PAL/NTSC/AUTO) YPbPr (576p, 720p, 1080i) HDMI (576p, 720p, 1080i)
• OS Language:	English, French, German, Spanish, Italian, Portuguese, Polish, Swedish,
• Power Supply:	DC: 5V/1A; AC input: 110~240V, 50~60HZ
• Operating Temp:	0°C ~ 60°C
• Product Dimensions:	7.5 X 7.5 X 2.9 cm
• Contents Include:	LHD56, AV & HDMI cable, 3.5mm Audio cable, power supply, remote control
* This player will loop both image and video file formats simultaneously	

<b>LHD76 Palm Sized Media Player 1080p Output</b>	
• Video Format:	H.264, H.263, VC-1, MPEG1, MPEG2, MPEG4, MKV, MOV, AVI, WMV, RMVB, TS, MPG, M2TS, VOB, DAT
• Photo Format:	JPEG, BMP, GIF, PNG, TIFF
• Audio Format:	MP3( code rate 8Kbps - 320Kbps)/WMA/WAV/ACC/OGG
• External Subtitles:	SMI, SRT, ASS, SSA.
• Storage Options:	SD/SDHC/MMC/USB2.0 (connect to external hard disk)
• File system:	FAT16, FAT32, NTFS
• Input Interface:	USB (High speed USB2.0 host), SD / MMC
• Output Interface:	CVBS (PAL/NTSC/AUTO) YPbPr (480p, 720p, 1080p) HDMI (480p, 720p, 1080p)
• OS Language:	English, French, German, Spanish, Italian, Portuguese, Polish, Swedish,
• Power Supply:	DC: 5V/1A; AC input: 110~240V, 50~60HZ
• Operating Temp:	0°C ~ 60°C
• Product Dimensions:	7.5 X 7.5 X 2.9 cm
• Contents Include:	LHD76, AV & HDMI cable, 3.5mm Audio cable, power supply, remote control

<b>MP1080 Network Media Player - Standalone, Real-Time, Internet Operating Modes 420p, 720p, 1080p Outputs</b>	
• Video Format:	MPEG 1 (.dat), MPEG2 (.mpg), MPEG4 (.avi, .divx), WM9 (.wmv) output at 1080p or less
• Photo Format:	JPEG (.jpg, .jpeg) - Support resolution up to 4096 x 4096 (max output resolution is 1920 x 1080)
• Audio Format:	Dolby Digital 5.1 (Group A), MPEG 1 (Layers 1 and 2), MPEG 1 (MP3), MPEG 4 AAC (Low Complexity, 5.1), Windows Media Audio, 16 bit Linear PCM
• Storage Format:	Compact Flash (up to 8GB) or USB Flash Drive
• Video Output:	VGA/HDMI (480p, 720p, 1080p)
• Audio Output:	Stereo Phone Jack
• Power Supply:	DC: 5V/1A; AC input: 110~240V, 50~60HZ
• Operating Temp:	0°C ~ 60°C
• Product Dimensions:	171 x 102 x 45 mm
• Contents Include:	MP1080, Remote Control, Power Supply

Digital Imaging Source  
 26 Main St.  
 Hilton, NY 14468  
 (585) 301-4980

*Call Us Today For Pricing...Quantity Discounts Available!*